



# SYSTEM FEATURES

Quickly and easily interchange multiple cameras and lenses Compact size and weight allows affordable transport as freight or excess baggage

No ITAR or EAR restrictions

Compatible with most FAA and EASA approved aircraft mounts

Easily integrated onto a wide variety of mounting platforms

6-axis gyro stabilized with look down capability

Windowless operation option for brilliant imagery without reflections

Fiber optic video data transfer for clean 3GHz imagery

State of the art electronics and design techniques deliver unshakable stability and ultimate functionality

Customizable graphics overlay for real time operator feedback

Auto or Steerable horizon with the most advanced steering capabilities on the market

Inverted operation using auto-position detectors

Remote controlled polarized filter rotation, rain deflector and other accessories available

# SYSTEM SPECIFICATIONS

# **STABILIZATION**

6-axis with no gimbal lock High performance non-ITAR sensors Distributed Multi-processor closed loop servo control system Proprietary gimbal control algorithms

# GIMBAL FIELD OF VIEW

Pan: 360 degrees continuous (via electrical and optical rotary joints)

Tilt: +45 to -140 degrees

Roll: +-85 degrees (steerable or auto horizon)

Max slew rate: 100 deg/sec

# DATA / COMMUNICATION

Fiber Optic lines **CAN Bus** RS 422 Serial Bus Ethernet

#### WEIGHT

Turret with max payload less than 55kg (122lbs) Operator control unit 2.7kg (6lbs) Junction control box 4kg (9lbs) External cable set: 2.5kg (5.5lbs)

#### **POWER**

19-72 VDC 20 Amps Max draw (at 19VDC)

#### ENVIRONMENTAL

Operating Temperature: -20 to +50 degrees C

## OPERATOR CONTROL UNIT

Liahtweiaht Customizable video overlay (Monitor Output) Recess for camera remotes such as: Sony RM-B750 Arri RCU-4 Other control layouts available upon request

## **CAMERA OPTIONS**

Arri Alexa M **RED Dragon RED Epic** Sonv HDC 2500 Sony F55 Canon C500 Other cameras on request

# **LENS OPTIONS**

Canon 30-300 Canon 14.5-60 Angenieux 15-40 Angenieux 17-80 Angenieux HR 25-250 Fujinon 42x13.5 Fujinon 42x9.7 Fujinon 18-85 Other lenses on request Interchangeable filters on request

## **OPTIONS**

GPS Geo pointing Auto tracking Remote controlled polarized filter rotation Window or rain deflector for environmental protection

Manufacturer reserves the right to change specification to reflect improvements and or changes in technology at any time